


Polymides

Polyimides


- **B-426** High Temperature Amber Polyimide
- **B-457** High Temperature White Polyimide
- **B-477** Static Dissipative Polyimide
- **B-478** Static Dissipative Polyimide
- **B-479** Static Dissipative Polyimide



Order Reference	Diagram	Material	Labels per Roll	Colour	Dimensions – mm		Maximum Bar Code Characters	Through Hole Technology Top	Through Hole Technology - Bottom	Surface Mount Technology (SMT)	After Process
					A	B					
PTL-1-426	▲	B-426	750	Amber	6.35	6.35	0	●	●	●	●
PTL-3-426	▲	B-426	500	Amber	9.53	9.53	0	●	●	●	●
PTL-4-426	▲	B-426	500	Amber	10.16	10.16	0	●	●	●	●
PTL-6-426	▲	B-426	750	Amber	12.70	6.99	0	●	●	●	●
PTL-9-426	▲	B-426	750	Amber	16.51	5.08	2	●	●	●	●
PTL-10-426	▲	B-426	750	Amber	19.05	6.35	2	●	●	●	●
PTL-13-426	▲	B-426	750	Amber	22.86	6.35	4	●	●	●	●
PTL-16-426	▲	B-426	500	Amber	25.40	9.53	4	●	●	●	●
PTL-17-426	▲	B-426	500	Amber	25.40	12.70	6	●	●	●	●
PTL-25-426	▲	B-426	750	Amber	31.75	6.35	6	●	●	●	●
PTL-27-426	▲	B-426	750	Amber	38.10	3.18	8	●	●	●	●
PTL-28-426	▲	B-426	750	Amber	38.10	6.35	8	●	●	●	●
PTL-2-426	▲	B-426	100	Amber	50.80	6.35	11	●	●	●	●
PTL-1-457	▲	B-457	750	White	6.35	6.35	0	●	●	●	●
PTL-3-457	▲	B-457	500	White	9.53	9.53	0	●	●	●	●
PTL-4-457	▲	B-457	500	White	10.16	10.16	0	●	●	●	●
PTL-6-457	▲	B-457	750	White	12.70	6.99	0	●	●	●	●
PTL-9-457	▲	B-457	750	White	16.51	5.08	2	●	●	●	●
PTL-10-457	▲	B-457	750	White	19.05	6.35	2	●	●	●	●
PTL-13-457	▲	B-457	750	White	22.86	6.35	4	●	●	●	●
PTL-14-457	▲	B-457	750	White	25.40	4.75	4	●	●	●	●
PTL-16-457	▲	B-457	500	White	25.40	9.53	4	●	●	●	●
PTL-25-457	▲	B-457	750	White	31.75	6.35	6	●	●	●	●
PTL-27-457	▲	B-457	750	White	38.10	3.18	8	●	●	●	●
PTL-28-457	▲	B-457	750	White	38.10	6.35	8	●	●	●	●
PTL-2-457	▲	B-457	100	White	50.80	6.35	11	●	●	●	●
PTL-1-477	▲	B-477	750	White	6.35	6.35	0	●	●	●	●
PTL-3-477	▲	B-477	500	White	9.53	9.53	0	●	●	●	●
PTL-9-477	▲	B-477	750	White	16.51	5.08	2	●	●	●	●
PTL-10-477	▲	B-477	750	White	19.05	6.35	2	●	●	●	●
PTL-14-477	▲	B-477	750	White	25.40	4.75	4	●	●	●	●
PTL-25-477	▲	B-477	750	White	31.75	6.35	6	●	●	●	●
PTL-27-477	▲	B-477	750	White	38.10	3.18	8	●	●	●	●
PTL-28-477	▲	B-477	750	White	38.10	6.35	8	●	●	●	●
PTL-2-477	▲	B-477	100	White	50.80	6.35	11	●	●	●	●
PTL-1-478	▲	B-478	750	White	6.35	6.35	0	●	●	●	●
PTL-3-478	▲	B-478	500	White	9.53	9.53	0	●	●	●	●
PTL-3-478	▲	B-478	500	White	9.53	9.53	0	●	●	●	●
PTL-4-478	▲	B-478	500	White	10.16	10.16	0	●	●	●	●
PTL-6-478	▲	B-478	750	White	12.70	6.99	0	●	●	●	●
PTL-9-478	▲	B-478	750	White	16.51	5.08	2	●	●	●	●
PTL-10-478	▲	B-478	750	White	19.05	6.35	2	●	●	●	●
PTL-13-478	▲	B-478	750	White	22.86	6.35	4	●	●	●	●
PTL-14-478	▲	B-478	750	White	25.40	4.75	4	●	●	●	●
PTL-16-478	▲	B-478	500	White	25.40	9.53	4	●	●	●	●
PTL-17-478	▲	B-478	500	White	25.40	12.70	6	●	●	●	●
PTL-25-478	▲	B-478	750	White	31.75	6.35	6	●	●	●	●
PTL-27-478	▲	B-478	750	White	38.10	3.18	8	●	●	●	●
PTL-28-478	▲	B-478	750	White	38.10	6.35	8	●	●	●	●

● Yes, this material will work with this application.
x No, this material does not work with this application.

Polymides



Polyimides *continued from page 26*

Order Reference	Diagram	Material	Labels per Roll	Colour	Dimensions – mm		Maximum Bar Code Characters	Through Hole Technology Top	Through Hole Technology - Bottom	Surface Mount Technology (SMT)	After Process
					A	B					
PTL-2-478	▲	B-478	100	White	50.80	6.35	11	●	●	●	●
PTL-1-479	▲	B-479	750	White	6.35	6.35	0	●	●	●	●
PTL-3-479	▲	B-479	500	White	9.53	9.53	0	●	●	●	●
PTL-4-479	▲	B-479	500	White	10.16	10.16	0	●	●	●	●
PTL-6-479	▲	B-479	750	White	12.70	6.99	0	●	●	●	●
PTL-9-479	▲	B-479	750	White	16.51	5.08	2	●	●	●	●
PTL-10-479	▲	B-479	750	White	19.05	6.35	2	●	●	●	●
PTL-13-479	▲	B-479	750	White	22.86	6.35	4	●	●	●	●
PTL-14-479	▲	B-479	750	White	25.40	4.75	4	●	●	●	●
PTL-16-479	▲	B-479	500	White	25.40	9.53	4	●	●	●	●
PTL-17-479	▲	B-479	500	White	25.40	12.70	6	●	●	●	●
PTL-25-479	▲	B-479	750	White	31.75	6.35	6	●	●	●	●
PTL-27-479	▲	B-479	750	White	38.10	3.18	8	●	●	●	●
PTL-28-479	▲	B-479	750	White	38.10	6.35	8	●	●	●	●
PTL-2-479	▲	B-479	100	White	50.80	6.35	11	●	●	●	●

● Yes, this material will work with this application.
x No, this material does not work with this application.